



Installation Instructions – “T” Bracket Kit™

Note to Dealers: If you install this product for the consumer, please provide him/her with this owner's manual after installation.

Thank you for purchasing the Profile Design “T” Bracket™ Kit. This kit is to be used a replacement part for Profile Design aerobars that use a standard, non-flip ZB Bracket. Please read these instructions thoroughly before attempting to install this item. Proper installation is required for compliance with Profile Design's warranty policy. If you are not familiar with the installation of aerobars or their accessories, please seek the assistance of your local Profile Design dealer by logging on to www.profile-design.com and using "dealer search" or by calling Profile Design's customer service number.

Tools and materials required: 5mm Allen wrench, Torque wrench

1. Threaded areas have been pre-treated by Profile Design during production with a special blue thread locking compound. This special compound is easy to detect on the threads of all bolts provided. If you cannot detect this thread locking compound or if you have cleaned it off through normal maintenance, re-apply a suitable blue thread locking compound as available from Loctite® or another company before assembly.
2. The “T” Bracket™ Kit will fit many current Profile Design aerobars including Carbon Stryke™, Carbon X™, Alumin X™, & CBX Pro™. Please determine the aerobar model you have before proceeding with this installation. If you need assistance in determining your bar model, you may contact Profile Design at (310) 884-7756 ext. 161 (or send an email to warranty@profile-design.com).
3. Remove the left and right adjustable arm bridges that are attached to the top brackets of your current aerobar. Place a standard height “T” bracket (#1) on top of each top bracket making sure the “gear” interface between the “T” bracket and the top bracket fits together. Place a convex washer (#2) into the recessed portion of the top bracket and, using the 5mm Allen wrench, tighten the M6x18 (#3) flat head bolts to a torque of 60in-lbs (6.7Nm). To adjust the angle of the “T” bracket, loosen the M6x18 flat head bolt, rotate the bracket to the desired angle, and re-tighten to a torque of 60in-lbs (6.7Nm) Note that extreme angle adjustment will limit the ability of the arm troughs to align correctly. If more height is desired for a customized fit you can substitute a “T” riser bracket (#4) for the standard bracket. If you decide to use the riser you must also substitute the M6x30 (#5) flat head bolts for the M6x18 (#3) flat head bolts. Using the 5mm Allen wrench, tighten the M6x30 (#5) flat head bolts to a torque of 60in-lbs (6.7Nm). Using the “T” riser bracket eliminates the need to use the standard riser post.
4. Re-install your armrests, using the M6x16 (#6) flat head bolts provided. Tighten these bolts to a torque of 30 in-lbs (3.4Nm).
5. Recheck the bolts for tightness after first usage and periodically thereafter to insure secure attachment of the aerobar.

▲ WARNING

- Any failure to follow these warnings can result in breakage and or slippage of this Profile Design product causing a loss of control of the bicycle with serious injuries. [AP1100-1-1]
- A creaking component can be a sign of potential problems. Make sure all contact surfaces between components are clean, all bolt threads are greased or are treated with proper thread lock and tightened to Profile Design's (or the bike manufacturer's) specifications and all components are properly sized to fit together. If you continue to experience creaking stop using the Profile Design component and call Profile Design customer service. [AP0601-2-2]
- Under tightening a bolt can result in a part coming loose while riding and an over tightened bolt can break unexpectedly while riding also resulting in a loss of control. All bolts must be tightened to Profile Design's (or the bike manufacturer's) specifications. [AP1100-3-1]
- Periodically, closely examine all surfaces of this Profile Design component (after cleaning) in bright sunlight to check for any small hairline cracks or fatigue at "stress points" (such as welds, seams, holes, points of contact with other parts etc.). If you see any cracks, no matter how small, stop using the part immediately and call Profile Design customer service. [AP0302-4-2]
- Whenever you install any new component on your bike make sure you thoroughly try it out close to home (with your helmet) where there are no obstacles or traffic. Make sure everything is working properly before going off on a ride or to a race. [AP1100-5-1]
- Racing (road, mountain or multi-sport) places extreme stress on bicycles and their components (like it does riders) and significantly shortens their usable life. If you participate in these types of events, the lifetime of the product may be significantly shortened depending upon the level and amount of racing. The “normal wear” of a component may differ greatly between competitive and non-competitive uses, which is why professional level riders often use new bikes and components each season as well as having their bikes service by professional mechanics. Particular care should be placed in the regular examination of your bicycle and it's components to insure your safety. [AP1100-6-1]
- A number of factors can reduce the life of this component to less than its warranty period. Rider size and/or strength, high mileage, rough terrain, abuse, improper installation, adverse weather conditions and crashes or accidents can all contribute to the shortening of the life of this component. The more factors that are met, the more the life of the component is reduced. [AP0801-7-2]
- Make sure you periodically recheck ALL aerobar bolts for tightness as indicated. Many of these bolts can loosen due to road vibration, which can cause possible breakage and loss of control. Make sure only the Profile Design supplied bolts are used. [AB1100-1-1]
- Aerobars can require riding positions that are new or different to many riders. It is advisable to practice using these bars in a low traffic area to become accustomed to any changes in the steering or handling characteristics of the bike. Please exercise caution when using these types of handlebars for the first time. Also make sure that you continue to look forward when riding and do not look down towards the ground. [AB1100-2-1]
- If you ever crash and the handlebar, aerobar OR stem is damaged in any way, (slight bends or scrapes) ALL ADJOINING PARTS should be replaced as there may be undetectable damage to either part. Call Profile Design customer service and ask about our “Crash Replacement Policy”. [AB1100-3-1]
- Some lightweight aluminum and carbon fiber handlebars are not compatible with aerobar assemblies; please refer to the handlebar manufacturer's installation instructions for this information. [AB1100-4-1]
- Whenever a bike equipped with an aero bar is placed on a roof rack, remove the armrest pads (if they are Velcro attached). Profile Design Warranty does not cover pads lost during transport. [AB101-6-1]

Profile Design, LLC

Worldwide Limited Warranty

Profile Design LLC warrants to the original retail purchaser (“you”) that the Profile Design product for which they received this warranty is free from defects in material and workmanship for two years from the date of original retail purchase. This warranty is not transferable to a subsequent purchaser. Profile Design's sole obligation under this warranty is to repair or replace the product, at Profile Design's option. Profile Design must be notified in writing of any claim under this warranty within 60 days of any claimed lack of conformity of the product.

Warranty Limitations

The duration of any implied warranty or condition, of merchantability, fitness for a particular purpose, or otherwise, on this product shall be limited to the duration of the express warranty set forth above. In no event shall Profile Design be liable for any loss, inconvenience or damage, whether direct, incidental, consequential or otherwise, resulting from breach of any express or implied warranty or condition, of merchantability, fitness for a particular purpose, or otherwise with respect to this product, except as set forth herein. Some states or countries do not allow limitation on how long an implied warranty lasts and some do not allow exclusions or limitations of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights, which may vary, from location to location. This warranty will be interpreted pursuant to the laws of the United States. The original English language version/meaning of this warranty controls over all translations and Profile Design is not responsible for any errors in translation of this warranty or any product instructions. This warranty is not intended to confer any additional legal, jurisdictional or warranty rights to you other than those set forth herein or required by law. If any portion of this warranty is held to be invalid or unenforceable for any reason, such finding will not invalidate any other provision. For products purchased in countries other than the United States please contact Profile Design's authorized distributor in that respective country.

Warranty Service Options

To obtain service under this warranty you must either:

(1) Bring or send your Profile Design product, together with this warranty, the retail seller's original receipt or other satisfactory proof of the date of purchase to the retailer where you purchased the item or another authorized Profile Design retailer, or

(2) Send your Profile Design product (with the return authorization number on the outside of the shipping container and affixed to the product), together with the retail seller's original receipt or other satisfactory proof of the date of purchase to Profile Design 2677 El Presidio St. Long Beach, CA 90810 USA. You must first obtain a return authorization number by calling Profile Design at (310) 884-7756 ext. 161 (or send an email to warranty@profile-design.com) prior to returning the product to Profile Design.

Profile Design may require that you complete and sign a warranty replacement request form before processing your warranty claim.

Any postage, insurance or other shipping costs incurred in sending your Profile Design product for service under either option above is your responsibility. Profile Design will not be responsible for products lost or damaged in shipping.

For products purchased in countries other than the United States please contact Profile Design's authorized distributor in the country where the product was purchased. They can be found on our website at www.profile-design.com

Crash Replacement Policy

Profile Design understands that crashes can happen. As a result Profile Design will attempt to ease the pain by offering you a replacement product for 30% below Profile Design's current suggested retail price in your respective country. All other provisions of this warranty apply and the procedures outlined for warranty service apply also to the crash replacement policy. Profile Design will make the final decision on whether the part will be covered under the crash replacement policy.

Warranty Exclusions

Retailers and sellers of Profile Design products are not authorized to modify this warranty in any way. It is your responsibility to regularly examine the product to determine the need for normal service or replacement. This warranty does not cover the following:

- Products that have been modified, neglected or poorly maintained, used for commercial purposes, misused or abused or involved in accidents.
- Damage occurring during shipment of the products (such claims must be presented directly to the shipper).
- Damage to products resulting from improper assembly or repair, the use or installation of parts or accessories not compatible with the original intended use of the product, or the failure to follow the product warnings and usage instructions.
- Damage or deterioration to the surface finish, aesthetics or appearance of the product.
- The labor required to remove and/or re-fit and re-adjust the item covered by this warranty.
- Normal wear to the product.
- Any products for which the consumer does not follow the warranty procedures outlined above.

For the current version of this warranty please visit our website at www.profile-design.com

(© June 2003 Profile Design)

"T" Bracket Kit™ Parts List			
Qty	Part #	Ref. #	Part Description
2	189287	1	Bracket-"T" Style Standard
2	201008	2	Convex Washer
2	313618	3	Bolt-M6x18 Flat Head Black
2	189288	4	Bracket-"T" Style Riser
2	313630	5	Bolt-M6x30 Flat Head Black
4	313616	6	Bolt-M6x16 Flat Head Black